



LCD Display Product Specification

	
Model Name: 32LF88	
1.Panel Spec	
Size	31.51" diagonal
Backlight	DLED direct Type
Maximum resolution	1366×768
Contrast ratio (Typ)	1200: 1
Response time(Typ)	7ms
Display scale	16:09
Viewing angle(CR>10)	Typ(H:178°,V:178°)
Display Colors	16.7 M
Color Gamut(NTSC)	Min: 65% Typ: 68%
LCM Center Luminance of White	Min:200cd/m2;Typ:240cd/m2
Local dimming	nonsupport
Uniformity of Luminance	≥70%
2.Hardware Information	
Audio power(Output)	6W+6W
HDMI 1.4 (HDCP 1.4)	2
USB 2.0	1
VGA	1
AV In	1
Audio Out	1(optional)
3.Software Function	
MTS/NICAM	NICAM
Sleep time setting	YES
Teletext	Yes
DOLBY	Yes
HDMI-ARC	HDMI-1
HDMI-CEC	YES
OTA	NO
Hotel mode	n/a
4.Structure Information	
Size (without stand) LxWxH	720×82×425mm
Size (withstand) LxWxH	720×172×448mm
Size (carton) LxWxH	778×109×468mm
Net Weight (without stand)	3.85kg
Net Weight (withstand)	3.9kg
Gross Weight (without stand)	4.85kg
Gross Weight (withstand)	4.9kg
Size (VESA Mount)	200 x 200mm
5.Power Management&Safety&Certificate	
Power input	220VAc

Fire rating	UL94-HB75
Standby power	≤0.5W
Rated power	55W
Working condition	Temperature:5°C~40°C, Humidity:10%~80%, Atmosphere:86KPa~ 106KPa
Storage condition	Temperature:-20°C~55°C, Humidity:10%~80%, Atmosphere:86kPa ~ 106kPa
6.Accessory	
Stand	1PCS
Remote control	1PCS
Instruction Manual	1PCS