





# LED Display Product Specification

|   |   |  |   |
|---|---|--|---|
|  |  |  |  |
| <b>Model Name: 43LF88</b>   |   |  |   |
| <b>1.Panel Spec</b>   |   |  |   |
| Size  | 42.51" diagonal   |  |   |
| Backlight   | DLED direct Type  |  |   |
| Maximum resolution  | 1920×1080   |  |   |
| Contrast ratio (Typ)  | 4000:1  |  |   |
| Response time(Typ)  | 8ms   |  |   |
| Display scale   | 16:09   |  |   |
| Viewing angle(CR>10)  | Typ(H:178°,V:178°)  |  |   |
| Display Colors  | 16.7 M  |  |   |
| Color Gamut(NTSC)   | ≥NTSC 68%   |  |   |
| LCM Center Luminance of White   | Min:220cd/m2;Typ:260cd/m2   |  |   |
| Local dimming   | nonsupport  |  |   |
| Uniformity of Luminance   | ≥70%  |  |   |
| <b>2.Hardware Information</b>   |   |  |   |
| Audio power(Output)   | 8W+8W   |  |   |
| HDMI 1.4 (HDCP 1.4)   | 2   |  |   |
| USB 2.0   | 1   |  |   |
| AV In   | 1   |  |   |
| Audio Out   | 1   |  |   |
| SPDIF Out   | 1(optical)  |  |   |
| <b>3.Software Function</b>  |   |  |   |
| Picture freezing  | YES   |  |   |
| MTS/NICAM   | NICAM   |  |   |
| Sleep time setting  | YES   |  |   |
| DOLBY   | Yes   |  |   |
| HDMI-ARC  | HDMI-1  |  |   |
| HDMI-CEC  | YES   |  |   |
| OTA   | NO  |  |   |
| Hotel mode  | n/a   |  |   |
| <b>4.Structure Information</b>  |   |  |   |
| Base model name   | BCCP-43 Straight fixed plastic bottom base  |  |   |
| Size (without stand) LxWxH  | 956×87×556mm  |  |   |
| Size (withstand) LxWxH  | 956×172×580mm   |  |   |
| Size (carton) LxWxH   | 1060×126×636mm  |  |   |
| Net Weight (without stand)  | 6.1kg   |  |   |
| Net Weight (withstand)  | 6.2kg   |  |   |
| Gross Weight (without stand)  | 8.1kg   |  |   |
| Gross Weight (withstand)  | 8.2kg   |  |   |
| Size (VESA Mount)   | H200×V200mm   |  |   |

**5.Power Management&Safety&Certificate**

|                   |  |
|-------------------|--|
| Power input       | 100~240VAc   |
| Fire rating       | UL94-HB75  |
| Standby power     | ≤0.5W  |
| Rated power       | 75W  |
| Working condition | Temperature: 5°C~40°C humidity: 20%~80% atmosphere: 86KPa~106KPa   |
| Storage condition | Temperature: -20°C~55°C humidity: 20%~80% atmosphere: 86kPa~106kPa |

**6.Accessory**

|                    |      |
|--------------------|------|
| Stand              | 1PCS |
| Remote control     | 1PCS |
| Instruction Manual | 1PCS |