



LCD Display Product Specification

	
Model Name: 65S79U	
1.Panel spec	
Size	64.53" diagonal
Backlight	DLED direct Type
Maximum resolution	3840×2160
Contrast ratio (Typ)	1200:1
Response time(Typ)	8ms
Display scale	16:09
Viewing angle(CR>10)	Typ(H:178°,V:178°)
Display Colors	1.07G
Color Gamut(NTSC)	≥NTSC 62%
Local dimming	Nonsupport
Uniformity of Luminance	≥70%
LCM Center Luminance of White	Min:280cd/m2,Typ:330cd/m2
2.Hardware Information	
CPU Frame	ARM Cortex-A53/1.5GHz/Quad core
GPU	G52MP2/Dual core
RAM(DDR3)	1.5GB
ROM(Flash)	8GB
Audio power(Output)	8W+8W
WIFI(Type)	2T2R
USB 2.0	2
AV In	1(mini)
RJ-45	1
Audio Out	1
SPDIF Out	1(optical)
Bluetooth(Version)	V5.1
HDMI	3
3.Software Function	
MTS/NICAM	MTS
Sleep time setting	YES
DOLBY	YES
Teletext	YES
PVR	YES
HDMI-ARC	HDMI-1
HDMI-CEC	YES
Operation system	Android 11
OTA	YES
Hotel mode	n/a
4.Structure Information	
Base model name	BCDH-65 prismatic fixed hardware base
Size (without stand) LxWxH	1445×89×832mm

Size (withstand) LxWxH	1445×326×880mm
Size (carton) LxWxH	1588×152×938mm
Net Weight (without stand)	14.8kg
Net Weight (withstand)	15.3kg
Gross Weight (without stand)	19.6kg
Gross Weight (withstand)	20.1kg
Size (Wall hanging)	300 x 300mm
5.Power Management&Safety&Certificate	
Power input	100-240VAc
Fire rating	UL94-HB75
Standby power	≤0.5W
Rated power	Default: 160W
Working condition	Temperature: 5°C~40°C humidity: 20%~80% atmosphere: 86KPa~106KPa
Storage condition	Temperature: -20°C~55°C humidity: 20%~80% atmosphere: 86kPa~106kPa
6.Accessory	
Stand	1PCS
Remote control	1PCS
Instruction Manual	1PCS