



LCD Display Product Specification

	
Model Name: 75S9U	
1.Panel Spec	
Size	75"diagonal
Backlight	DLED direct Type
Maximum resolution	3840×2160
Contrast ratio (Typ)	1200:1
Response time(Typ)	8ms
Display scale	16:09
Viewing angle(CR>10)	Min(H:178°V:178°)
Display Colors	1.07 G
Color Gamut(NTSC)	≥NTSC 68%
Local dimming	nonsupport
Uniformity of Luminance	≥75%
LCM Center Luminance of White	Min.:280cd/m2;Typ.330cd/m2
2.Hardware Information	
CPU Frame	ARM Cortex-A53/1.5GHz/Quad core
GPU	G52MP2/Dual core
RAM(DDR3)	1.5GB
ROM(Flash)	8GB
Audio power(Output)	8W+8W
WIFI(Type)	2T2R
USB 2.0	2
AV In	1(mini)
RJ-45	1
Audio Out	1
SPDIF Out	1(optical)
Bluetooth(Version)	V5.1
HDMI	3
3.Software Function	
MTS/NICAM	MTS
Sleep time setting	YES
Teletext	YES
PVR	YES
DOLBY	YES
HDMI-ARC	HDMI-1
HDMI-CEC	YES
Operation system	Android 11
OTA	YES
Hotel mode	n/a
4.Structure Information	
Base model name	BCD2-75 Gemini Fixed Hardware Base
Size (without stand) LxWxH	1669×103×958mm
Size (withstand) LxWxH	1669×353×1020mm

Size (carton) LxWxH	1840×173×1095mm
Net Weight (without stand)	28.7kg
Net Weight (withstand)	29.2kg
Gross Weight (without stand)	37.4kg
Gross Weight (withstand)	37.9kg
Size (VESA Mount)	500 x 300 mm
5.Power Management&Safety&Certificate	
Power input	100-240VAc
Fire rating	UL94-HB75
Standby power	≤0.5W
Rated power	270W
Working condition	Temperature: 5°C~40°C humidity: 20%~80% atmosphere: 86KPa~106KPa
Storage condition	Temperature: -20°C~55°C humidity: 20%~80% atmosphere: 86kPa~106kPa
6.Accessory	
Stand(Optional)	1PCS
Remote control	1PCS
Instruction	1PCS